

Savroc – Advanced Coating Solutions

TripleHard® - Easy Coating Solution for Job Shop Professionals

Savroc develops advanced coatings with superior wear resistance, corrosion protection, and sustainability. Our patented TripleHard® coating outperforms Cr6, eliminating hazardous chemicals while meeting industry standards.

High hardness | Low friction | Cr³⁺-based | Cr⁶⁺ -free | Corrosion resistant

Key Points

- Operates at 55–65 °C
- 30% process efficiency
- Familiar Watts-like chemistry
- S7 automation and auto-dosing
- Industry 4.0 ready











Contact us:

Business Development +491627375960 □ alexander.gramm@savroc.com Savroc

+358443071409

iussi.raisa@savroc.com

 iussi.raisa@savroc.com



Scan to schedule a meeting or download more materials.







TripleHard® Coating Process Steps

1



Degreasing – Removes oils and organic contaminants. Rinse 2



Etching (10–60 s, e.g., H₂SO₄) – Removes oxides and activates the metal surface. Rinse 3



Nickel layer (1–10 min, optional) – Enhances adhesion and corrosion resistance. Rinse

4



TripleHard® plating (Cr³+, 5–20 min) – High hardness and wear resistance without Cr6+.Rinse

Additional Process Information

1. Deposition rate: $0.5-5 \mu m/min$ (depending on current density)

2. Operating temperature: ~55 °C

3. Bath type: Trivalent chromium (Cr³+), Cr6+-free

4. Integration: Retrofit-ready for most existing plating lines

Analytical Evidence




Coated parts




Dosing units



Plating line



Hardness



System setup



System setup

Schedule a meeting with our experts.

Discover real-world applicationsLearn about our exclusive industry partnerships

- +491627375960
- □ alexander.gramm@savroc.com
- Varikkokatu 2, FI-70620 Kuopio
- savroc.com
- **c** +358 443071409
- iussi.raisa@savroc.com

 iussi.raisa@savroc.com
- ♥ Varikkokatu 2, FI-70620 Kuopio
- savroc.com